



SINGLE AXLE BOX VAN TRAILER













	Roadster 220	Roadster 255 Unbraked Version	Roadster 255 Braked version	Cargo 1300	Roadster 300	Roadster 400
Payload	420 kg	400 kg	930 kg	855 kg	840 kg	810 kg
Ramp's weight capacity	No ramp	500 kg	500 kg	500 kg 750 kg (as extra)	500 kg 750 kg (as extra)	500 kg 750 kg (as extra)
Pullman	No	No	No	Yes	Yes	Yes
External dimensions (Lxlxh) en mm	3510x1610x1801	3690x1740x2010	3690x1740x2010	4250x2020x2020	4250x2050x2310	4450x2150x2370
Max. Gross Weight	750 kg	750 kg	1300 kg	1300 kg	1300 kg	1300 kg
Interior dimensions (Lxlxh) en mm	2200x1080x1150	2550x1250x1550	2550x1250x1550	3000x1520x1650	3000x1650x1520	3130x1660x2010
Floor	non-slip plywood	non-slip plywood 15 mm	non-slip plywood 15 mm	non-slip plywood 15 mm	non-slip plywood 15 mm	Aluminium 24 mm 5 years warranty
Galvanised steel chassis with aluminum extrusion framework	Yes	Yes	Yes	Yes	Yes	Yes
Wheel chocks	Yes	Yes	Yes	Yes	Yes	Yes
Interior light	No	No	No	Yes	Yes	Yes
Rear loading	Opening door	Ramp-door	Ramp-door	Ramp-door	Ramp-door	Ramp-door

DOUBLE AXLE BOX VAN TRAILER













Roadster 500	Roadster 700	Roadster 800	Roadster 900	Roadster 1000	Roadster 2000
1345 kg	1895 kg	2500 kg	2400 kg	2535 kg	2200 kg
500 kg 750 kg (as extra)	1000 kg	1000 kg	1000 kg	1500 kg	1500 kg
Yes	Yes	Yes	Yes	Yes	Yes
4450x2150x2370	4990x2330x2370	5650x2315x2440	6220x2315x2440	6250x2345x2365	6750x2530x2480
2600 kg (2600 kg as extra)	2600 kg	3500 kg	3500 kg	3500 kg	3500 kg
3130x1660x2010	3760x1810x2010	4360x2060x2060	4970x2060x2060	4970x2020x2060	5500x2200x2045
Aluminium 24 mm 5 years warranty					
Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes
Yes	Yes	Yes	Yes	Yes	Yes
Ramp-door	Ramp-door	Ramp-door	Ramp-door	Ramp with ramp extension	Ramp with ramp extension



Plywood





- Hot dip galvanized chassis
- Lockable rear door
- 2 wheel chocks
- jockey wheel diameter 48mm
- Axle 750 kg unbraked
- Protected lights
- "V" drawbar
- Tie-rings x4
- 1 handle
- 1 prop stand





RAMP DOOR COMBINATION



ROADSTER 255

braked trailer











Aluminium 5 year warranty



- Roof and front in one solid fiberglass part
- 18 mm plywood side walls
- Aluminium rear ramp door combination
- Shockproof mudguards
- Protected lights
- Tie-rings x4
- 2 prop stands
- Automatic jockey wheel with handle

OPTIONAL

- Composite side walls
- Aluminium side walls
- Lateral door with key lock





Unbraked Trailer



- Roof and front in one solid fiberglass part
- 18 mm plywood side walls
- Aluminium rear ramp door combination
- Shockproof mudguards
- Protected lights
- Tie-rings x4
- 2 prop stands
- Automatic jockey wheel

OPTIONAL

Side door with key lock



RAMP DOOR
COMBINATION



Our vans crafted for all drivers.

With these models, you don't need a special licence.

Designed to be **compact** and lightweight, these vans combine **robustness** and **manoeuvrability** for a **pleasant drive**, even for beginners







Simple. Efficient. Unlimited.

Book a trial today and discover the Debon difference.



RAMP DOOR

















- Roof and front in one solid fiberglass part
- Plywood side walls 18 mm with UV protection folder
- Aluminium ramp door combination
- Shockproof mudguards
- Protected lights
- Tie-rings x4
- 2 pro stands
- Automatic jockey with handle

OPTIONAL

- Aluminium side walls
- Lateral door with key lock
- Lateral sales flap.







Fiberglass bodywork

CARGO 1300

performance

- Exclusive aerodynamic design
- Rear aluminium ramp door combination
- Shockproof mudguards
- Protected lights
- Tie-rings x4
- 2 prop stands
- Automatic jockey wheel with handle

OPTIONAL

Side door with key lock









Pullman technology, the Debon difference.

A flagship **innovation** for our trailers, the **Pullman suspension** system significantly improves driving comfort by reducing while maintaining **stability** and **safety**, even when fully loaded.

ROADSTER 400



Composite



Fiberglass







- Roof and front in one solid fiberglass part
- 18 mm plywood side walls
- Aluminium floor
- Aluminium rear ramp door combination.
- Shockproof mudguards
- Protected lights
- Tie-rings x4
- 2 prop stands
- Automatic jockey wheel with handle

OPTIONAL

- Aluminium side walls
- Lateral door with key lock
- Lateral sales flap

















Composit



Fiberglass









- Roof and front in one solid fiberglass part
- 18 mm plywood side walls
- Aluminium floor
- Rear aluminium ramp door combination
- Shockproof mudguards
- Protected lights
- Tie-rings x6
- Automatic jockey wheel with handle

OPTIONAL

- · Aluminium side walls
- Lateral door with key lock
- Lateral sales flap



ROADSTER 700











- Roof and front in one solid fiberglass part
- Aluminium side walls
- Aluminium floor
- Rear aluminium ramp door combination
- Lateral door with kev lock
- Shockproof mudguards
- Shockproof maagaala
- Protected lights
- Tie-rings x8
- Wheels 14'
- Automatic jockey wheel with handle

OPTIONAL

· Lateral sales flap







ROADSTER 800 ROADSTER 900









- Roof and front in one solid fiberglass part
- Aluminum lateral walls and floor
- Rear aluminium ramp door combination
- Lateral door with key lock
- Shockproof mudguards
- Designed rear lamps
- Tie-rings x8
- Automatic jockey wheel with handle
- Wheels 14"

OPTIONAL

• Lateral sales flap



Your trailer tailored to fit your needs on the spot

With a variety of opening options, our trailers give you total flexibility for transporting, accessing and organising your equipment.









Lateral doors L/R

Ramp door combination (model 255 to 900)

Lateral sales flap



VEHICLE TRANSPORT



Fiberglass







- Roof and front in one solid fiberglass part
- Honeycomb composite side walls
- Aluminium ramp with ramp extension
- 2 lateral doors
- 2 Side flaps : width 2360mm x height 1320mm
- Shockproof mudguards
- Led lights
- Tie-rings x8
- Automatic jockey wheel
- Low-profile tires 13'
- Prop stands

OPTIONAL

- Slidding electric winch
- Leveling ramps +11cm



ROADSTER 2000

VEHICLE TRANSPORT











- Roof and front in one solid fiberglass part
- Aluminium side walls and floor
- Rear aluminium ramp
- 2 lateral doors
- · 2 Side flaps : width 2360mm x height 1320mm
- Shockproof mudguards
- Led lights
- Tie-rings x8
- Automatic jockey wheel
- Low-profile tires 12'
- Prop stands

OPTIONAL

- Slidding electric winch
- Leveling ramps +11cm





Stability. Safety. Performance.

Thanks to the **Pullman technology**, which **protects** your cars from vibrations and shocks throughout the journey, the **Roadster 1000 and 2000** are guaranteed with **optimum transport** for your vehicles.







ROADSTER GARDEN

Automatic tilting & secured locking

- V drawbar 1300 kg capacity
- Axles 750kg or 1350kg
- Jockey wheel
- Strong mudguards
- Tilting platform with gas damper assistance
- Strong ramp
- Many tying points

USEFUL DIMENSIONS



MODEL 150

Unladen weight = 275 kg (from)
Max. Gross Weight = 500 to 1200 kg



MODEL 175

Unladen weight = 372 kg (from) Max. Gross Weight = 750 to 1300 kg















ROADSTER PLATFORM

Automatic tilting & secured locking

- · V drawbar 1300kg
- Axle 750kg or 1350kg
- Jockey wheel
- Strong mudguards
- Tilting platform with gas damper assistance
- Anti slipping plywood floor
- Many tying points

USEFUL DIMENSIONS





Unladen weight = 270 kg (from)

Max. Gross Weight = 500 to 1300 kg
depending on braked category














ROADSTER MOTO

Automatic tilting & secured locking

- Strong axle
- Jockey wheel
- Easy and safe loading/ unloading for large and or heavy motorcycle
- Foot locking/unlocking pedal
- Adjustable for any tire dimensions
- Many tying points


USEFUL DIMENSIONS



Roadster Moto 1 Dimension

Unladen weight = 185 kg (from)

Max. Gross Weight = 500, 600 ou 750 kg



Roadster Moto 2 Dimension


Unladen weight = 355 kg (from)
Max. Gross Weight = 750 to 1300 kg





Roadster Moto 2










ROADSTER CAMP

- Hot dip galvanized chassis and parts.
- Aluminium anti slippling platform
- Jockey wheel
- Strong wheels with tires
 195/50 B10 "High Speed
 Trailer"
- Adjustable platform to load 1 mortorcycle or several bikes.
- Extra removable rack to place more material or bikes.

USEFUL DIMENSIONS



Unladen weight: 180 kg (from) PTAC: 500 or 750 kg

ROADSTER AUTO

- Tilting platform with additional ramps.
- Robust construction, hot dipped galvanised.
- Progressive tilting with gas damper.
- Many tying possibilities.


 Ideal for transporting small vehicles.

Available optionals:

- Spare wheel with bracket
- Manual winch with bracket
- Tie straps and wheel chocks

USEFUL DIMENSIONS

Unladen weight = 360 kg (from) Max. Gross Weight = 1 300 kg



















PWO ONE-WAY TIPPER

- Hot dip galvanized chassis
- Strong axle
- 18 mm plywood floor
- Removable aluminium drop sides 300 mm
- Heavy duty automatic jockey wheel

 • Protected front and rear
- lights
- Rectangular posts (no residue in the corners)

PW0 «ECO»

• Double acting hand pump

PW0 «LUX»

- Electro-hydraulic with
- battery
 Plywood floor with galvanised protection steel plate
- H-frame and 6 tie-rings

PW1.2 ONE-WAY TIPPER

- Hot dip galvanized chassis
- 2 strong axles
- 18 mm plywood floorRemovable aluminium drop sides 300 mm
- Heavy duty automatic jockey wheel
- Protected front and rear lights
- Rectangular posts (no residue in the corners)

PW1.2 «ECO»

• Double acting hand pump


PW1.2 «LUX»

- Electro-hydraulic with battery
- Plywood floor with galvanised protection steel plate
- H-frame and 6 tie-rings

USEFUL DIMENSIONS


PW₀


Unladen weight = 430 kg (from) Max. Gross Weight = 750 to 1500 kg as required



PW1.2

Unladen weight = 540 kg (from) Max. Gross Weight = 1100 to 2000 kg as required









Model presented with a tarpaulin



Model shown with an extra set of side panels



Model shown with a mesh extension

Model shown with an extra set of side panels






Model shown with a mesh extension, aluminium crutches and handrails

USEFUL DIMENSIONS


PW2.4

Unladen weight = 710 kg (from)
Max. Gross Weight = 1600 to 2600 kg as required




PW3.3

Unladen weight = 800 kg (from) Max. Gross Weight = 2700 to 3500 kg as required



PW3.6

Unladen weight = 800 kg (from) Max. Gross Weight = 2700 to 3500 kg as required



PW2.4 PW3.3 & PW3.6 THREE-WAY TIPPERS

PW2.4

- Hot dip galvanized chassis
- 2 strong axles
- 18 mm plywood floor with galvanised protection steel plate

- Heavy duty automatic jockey wheel
 Protected front and rear lights
 Electro-hydraulic pump with battery
 Integrated ramps rack with strips for noise reduction
- Rectangular posts (no residue in the corners)
- 6 tie rings
- 4 removable aluminium drop sides 350 mm
- Removable front H-Frame galvanised steel

PW3.3

- 195/50R13C or 185R14C wheels
- Exclusive colour : black anodized alu
- Integral cover for battery and hydraulic unit
- 8 tie rings

PW3.6

- 8 tie rings
- 195/50R13C or 185R14C wheels
- Integral cover for battery and hydraulic unit



PULLMAN 2 SUSPENSION

Developed in the R&D department of Cheval Liberté/ Debon, the PULLMAN 2 suspension frees you from the constraints of hitched transport and allows you to tow your trailer in complete safety while enjoying exceptional road comfort.

Suspension inspired by cars

Always closer to automotive technology, the PULLMAN 2 suspension, 4 independent wheels suspension is composed of 4 articulated arms on galvanized steel silentblocks associated with 4 large diameter springs and 4 hydraulic dampers.

Pullman: performance and comfort.







Spring helical



Individual suspension arm



Hydraulic shock absorber

Optimised centre of gravity.

With a center of gravity placed as close to the road as possible, the Debon Trailers have an optimized ground clearance.

The trailers stick to the road and absorb the hazards of the road. Both unloaded and loaded, vibrations are considerably reduced, thus guaranteeing a remarkable comfort of use.

Certified quality.

The PULLMAN 2 suspension combined with the aerodynamic design of the Cheval Liberté vans offers a real comfort of traction and contributes to the significant reduction of the fuel consumption of the towing vehicle.

The PULLMAN suspension is recognized as the best suspension for vans and tippers.

It is recommended by all trailer professionals. In a few words, technology, safety and comfort perfectly sums up the performance of the Pullman 2 suspension.



Standorte



WIEN

Am Stadtrand von Wien, 2km zur SCS 1230 Wien Altmannsdorfer Str. 200

Bernhard Berger Tel. 0664 60 94 94 06



LIEBOCH

Direkt an der A2, Abfahrt Lieboch 8501 Lieboch Johann-Humer-Straße 1

Alexander v. Ederen Tel. 0664 60 94 94 13



GUNSKIRCHEN

Am Stadtrand von Wels, Abfahrt Wels West 4623 Gunskirchen bei Wels Grünbach 10

Robert Bartulovic Tel. 0664 60 94 94 08



LINDACH

Direkt an der A1, Abfahrt Laakirchen Ost 4663 Lindach/Laakirchen Johannes Humer-Straße 1

Herbert Hirschvogl Tel. 0664 60 94 94 02



KRAMSACH

Direkt an der A12, Abfahrt Kramsach 6233 Kramsach Amerling 131a

Pierre Reichegger Tel. 0664 60 94 94 15



BAD GOISERN (HUMER PARTNER)

HUMER

Direkt an der B145 4822 Bad Goisern Bundesstraße 47

Alex Putz Tel. 0664 76 77 51 9



SULZ (HUMER PARTNER)

Direkt an der A14, Abfahrt Klaus 6832 Sulz Industriestraße 2

Bernhard Schöch Tel. 0699 17 15 31 31



KLAGENFURT (HUMER PARTNER)

Am Stadtrand von Klagenfurt, Abfahrt Klagenfurt-Ost St. Jakober Straße 40 9020 Klagenfurt am Wörthersee

László illes

Tel. 0463 477 67 12

Q GUNSKIRCHEN
Q LINDACH
Q BAD GOISERN (Humer Partner)

Q KLAGENFURT (Humer Partner)







Besuchen Sie uns auch auf Facebook, Instagram und YouTube!

Debon Cheval Liberté Group

Since 1995







info@debon-trailers.com debon-trailers.com







Your dealer